

Suitable for Ammonia



Features:

- **Body:** Forged steel, zinc plated
- **Non-backseating** packed type
- **Glass** 1/2" diameter
- **Mounting centers:** 10"-15"-20"
- **For mounting centers greater than 20"**, multiple gauge sets are recommended
- **Suitable for refrigerants** (including ammonia) and other industrial fluids non-corrosive to steel and synthetic rubber side-well packing (neoprene)
- **Temperature rating:** -20°F (-29°C) to +150°F (+65°C)
- **A complete liquid level gauge set** includes the following four components: 1 pc. upper valve ; 1 pc. lower valve; 1 pc. gauge glass; 1 pc. guard set
- **Recommended maximum working pressures for mounting centers:** 10"-20" See Table.
- **If glass tubing breaks**, loss of refrigerant is restricted by an automatic ball check at the inlet of each valve
- Glass length is always 1-11/16" less than mounting centers. Guard set length is always 23/4" less than mounting centers.

Catalog Number	Size Connection	Weight lbs.
5021 (Lower)	1/2" F.P.T.	1.0
5022 (Upper)	1/2" F.P.T.	1.0

Catalog Number	Mounting Center	Weight lbs.	MWP (psi)
PS95-10	10"	1	363
PS95-15	15"	1	330
PS95-20	20"	1	310

