

We Have *COMPLETE* Drop In Replacements for *Standard Receivers*.

STANDARD REFRIGERATION P/N	HENRY P/N	OVERALL SIZE (OD" x LG")	INLET CONN. (ODS)	OUTLET CONN. (ODS)
ASME VERTICAL W/VALVES				
UV-30	S-8510V	8 5/8 X 18	1/2"	1/2"
UV-40	S-8510W	8 5/8 X 24	5/8"	5/8"
UV-50	S-8510S	8 5/8 X 32	7/5"	7/8"
UV-70	S-8520W	10.75 X 28	1 1/8"	1 1/8"
UV-100	S-8520X	10.75 X 38	1 1/8"	1 1/8"
UV-125	S-8552C	12.75 X 36	1 1/8"	1 1/8"
UV-150	S-8552B	12.75 X 42	1 1/8"	1 1/8"
UV-200	S-8561H	14 X 46	1 3/8"	1 3/8"
UV-275	S-8572G	16 X 48	1 5/8"	1 5/8"
UV-350	S-8572F	16 X 60	1 5/8"	1 5/8"
UV-450	S-8582H	18 X 62	1 5/8"	1 5/8"
ASME VERTICAL				
UR-66	S-8530H	12.75 X 18	1-1/8"	1-1/8"
UR-174	S-8582E	18 X 24	1-5/8"	1-5/8"
UR-28	S-8510U	8 5/8 X 16	5/8"	5/8"
ASME HORIZONTAL W/VALVES				
RBV-3865	S-8639V	6 5/8 X 38	5/8"	5/8"
RBV-96145	S-8791C	14 X 96	1-5/8"	1-5/8"

*REFRIGERANT CAPACITY	R22	R134A	R404A/R507	R407C	R502
S-8510V	33.3	33.8	32.9	35.1	33.7
S-8520W	84.3	85.5	83.3	88.9	85.4
S-8530G	69.1	70.1	68.3	72.0	70.0
S-8582E	180.0	182.6	177.9	189.0	182.4
S-8510U	29.1	29.5	28.8	30.7	29.5
S-8639V	43.5	44.1	42.0	45.9	44.0
S-8791C	505.4	512.8	499.5	533.5	512.2
*Pumpdown capacity is at 90% of receiver volume at 90 deg.F.					



701 S. Main Street, Chatham, IL 62629, 1-800-96 HENRY



Think **HENRY** for your *LIQUID REFRIGERANT NEEDS...*

RECEIVERS



FEATURES:

- **High Pressure Design
- **Inlet and Outlet Valves Included
- **Relief and Drain Connections
- **Mounting Legs for Easy Installation
- **Other Sizes are Available for Custom
- **Vertical Units are Also Available
- **Higher Pressure Designs are Available for the New Refrigerants

LIQUID LEVEL COLUMNS



FEATURES:

- **All Steel Welded Construction, High Pressure Design
- **Fused Glass Cap Assemblies: Reflex Lens Included
- **Maximum Working pressure: 500 PSI
- **Frost Shield Available
- **Designed to Accept New Easy View Liquid Level Switch

LIQUID LEVEL SWITCHES



FEATURES:

- **Solid State Switch for Liquid Sensing
- **No Contact Level Sensing
- **Serviceable Without Loss of Refrigerant
- **Works Well With Oil, Refrigerants, or any Non-Hazardous Non-Corrosive Fluid
- **Glass Prism in Contact with Fluid Medium
- **Industry Approved for Nema 4 and 4X for Water Tight
- **Meets UL Standard #873 & #207 File Numbers E141577 & SA6720

For your custom, short lead time, and readily available components call Henry Technologies at **1-800-96-HENRY** or **1-217-483-2406**.

WWW.HENRYTECH.COM



701 S. Main Street, Chatham, IL 62629

